

**CHARACTERISTICS OF SANITRUX CARTS**
**BODY**

- Constructed of high impact, tinted, heavy duty, Class II fire retardant fiberglass.
- Molded in one piece with no joints, laps or seams.
- Bottoms of most carts are reinforced with 5/8 inch plywood, bonded to the body and completely encapsulated in fiberglass.
- Composite is resistant to acids, alkalis and most chemicals.
- Finish is smooth on the inside, lightly textured and sealed with a clear coat on the outside.

**FIRE RETARDANT PROPERTIES**

- Class II fire retardant classification in accordance with ASTM-E 1354
- Compliant: NFPA-1, UFC and California Title 19
- Carts are permanently marked with capacity and fire retardant classifications.
- Signed independent testing laboratory certificate substantiating the fire retardant properties and smoke data furnished upon request.

**FIRE LIDS**

- Self-closing, easy lift gas prop lid is attached to the truck body by a continuous, concealed stainless steel hinge.
- Lid support is equipped with a UL listed fusible link that melts at 212 degrees, allowing the lid to self-close.
- Lid perimeter is ringed with gray, non-marking rubber bumper.


**CASTERS**

		CAPACITY
<b>6" Performa</b>	round rubber	450 lbs each
<b>8" Performa</b>	round rubber	600 lbs each
Completely sealed, steel roller bearings, attractive zinc plate finish, thread guards		
<b>5x1½" Hi-Tech</b>	polyethylene	400 lbs each
Resistant to water, acid, alkaline, steel roller bearings, attractive zinc plate finish, thread guards		
<b>5"x2"</b>	Polyolefin	500 lbs each

**STANDARD COLORS**


Option: custom colors at market rate